

构造表

对数	导体			护套 标准厚度 (mm)	成品外径 约 (mm)	概算质量(kg/km)			
	公称截面积 (mm ²)	构 成 (根/mm)	外 径 (mm)			E V	V V	E E	EM EE/F
1	0.2	7/0.18	0.54	1.3	5.5	35	35	30	35
2				1.3	7.0	55	55	45	55
3				1.3	7.5	60	65	50	60
4				1.3	8.0	70	70	60	70
5				1.3	8.5	85	85	70	85
7				1.3	9.0	95	100	85	95
10				1.3	10.0	115	125	105	115
15				1.3	12.0	150	160	140	150
20				1.3	13.0	185	205	170	185
25				1.3	14.0	215	235	200	215
30				1.3	15.0	245	270	230	245
40				1.3	16.0	305	330	285	305
50				1.4	18.0	370	410	355	370
1	0.3	12/0.18	0.72	1.3	6.0	40	45	35	40
2				1.3	8.0	70	70	60	70
3				1.3	8.5	80	80	65	80
4				1.3	9.0	95	100	80	95
5				1.3	10.0	110	115	90	110
7				1.3	11.0	125	135	115	125
10				1.3	12.0	160	175	145	160
15				1.3	14.0	215	235	200	215
20				1.3	15.0	265	290	250	265
25				1.3	17.0	315	350	300	315
30				1.4	18.0	370	405	350	370
40				1.5	20.0	475	510	450	475
50				1.6	23.0	595	640	560	595
1	0.5	20/0.18	0.93	1.3	7.0	55	55	50	55
2				1.3	9.5	100	105	80	100
3				1.3	10.0	115	115	100	115
4				1.3	11.0	135	145	120	135
5				1.3	12.0	160	170	140	160
7				1.3	13.0	180	195	165	180
10				1.3	15.0	235	250	220	235
15				1.4	17.0	325	355	305	325
20				1.4	19.0	415	450	390	415
25				1.5	21.0	505	555	465	505
30				1.6	23.0	605	650	565	605
40				1.7	25.0	765	830	720	765
50				1.8	29.0	935	1030	880	935
1	0.75	30/0.18	1.14	1.3	7.5	65	70	60	65
2				1.3	11.0	125	130	110	125
3				1.3	12.0	145	155	130	145
4				1.3	13.0	180	190	160	180
5				1.3	14.0	215	230	195	215
7				1.3	15.0	245	270	230	245
10				1.4	17.0	325	355	310	325
15				1.5	21.0	465	505	435	465
20				1.6	23.0	605	655	570	605
25				1.7	26.0	735	800	690	735
30				1.7	27.0	850	925	800	850
1	0.9	7/0.4	1.2	1.3	7.5	70	75	65	70
2				1.3	11.0	130	140	115	130
3				1.3	12.0	155	165	140	155
4				1.3	13.0	190	200	175	190
5				1.3	14.0	230	240	205	230
7				1.3	15.0	260	290	250	260
10				1.4	17.0	350	390	340	350
15				1.5	21.0	500	540	470	500
20				1.6	23.0	640	700	610	640
25				1.7	26.0	785	860	750	785
30				1.7	27.0	905	1000	860	905
1	1.25	7/0.45	1.35	1.3	8.5	80	85	75	80
2				1.3	12.0	155	160	130	155
3				1.3	14.0	185	200	170	185
4				1.3	15.0	230	250	215	230
5				1.3	16.0	270	290	255	270
7				1.4	17.0	325	355	305	325
10				1.5	19.0	435	475	410	435
15				1.6	24.0	630	690	600	630
20				1.7	26.0	805	880	760	805
25				1.8	29.0	985	1100	930	985
30				1.9	31.0	1150	1270	1050	1150
1	2.0	37/0.26	1.83	1.3	9.5	115	125	105	115
2				1.3	14.0	215	225	200	215
3				1.3	15.0	265	290	240	265
4				1.4	17.0	335	355	310	335
5				1.4	19.0	400	430	365	400
7				1.5	20.0	495	515	465	495
10				1.6	24.0	675	720	640	675
15				1.8	28.0	970	1050	910	970
20				1.9	32.0	1250	1350	1180	1250

※导体是JIS C3152标准规定的镀锡绞合软铜线。

备考：也可以按JIS C3102标准生产绞合软铜线。

注) 成品外径及概算质量是指编织屏蔽规格的产品。